

Disclaimer

Legal disclaimer

This guide and its contents (the "Guide") are provided by NXGEN. All rights to the Guide and to the intellectual property embodied in it — including, without limitation, trademarks, trade names, logos and similar marks appearing in or on it — are protected by law. All right, title and interest in the Guide and in any related intellectual property rights belong to and remain with NXGEN and its licensors.

The Guide is provided free of charge, "as is" and for informational purposes only, without warranty of any kind. It is neither intended nor suitable to establish any legal relationship between the reader and NXGEN or its affiliates, including, without limitation, any obligation of NXGEN or its affiliates toward the reader.

The obligations of NXGEN and its affiliates in respect of NXGEN products or services purchased by a customer are governed exclusively by the terms of the agreement under which those products or services were purchased.

For clarification

The reader bears the entire risk as to the use, results and performance of the Guide. To the fullest extent permitted by applicable law, NXGEN disclaims and excludes all warranties, whether statutory, express or implied — including, without limitation, implied warranties of merchantability, fitness for a particular purpose, title and non-infringement of third-party rights — as well as any liability or warranty arising from suggestions, specifications or samples related to the Guide.

Average Operator Processing Time

Updated 8 October 2026

experience — not included in the PDF

Summary

Average Operator Processing Time shows the team-wide average time from an Operator taking responsibility for a site or alarm to closing its alarms.

How to read it

- About 30–90 seconds per alarm — generally healthy.
- Under 15 seconds — may indicate bulk-closing or insufficient investigation.
- Over 3 minutes — may indicate difficult events, workflow friction, training needs, or a technical problem.

Treat these ranges as investigation signals, not automatic pass/fail rules.

What affects the metric

- Alarm complexity and video length.
- Number and density of devices at the site.
- Operator experience and training.
- Network or playback delays.
- Use of single-alarm versus bulk-close actions.

How to use it

Compare processing time with Alarms Handled , Picked Sites , Unique Devices , and closure-tag distribution. High throughput with a healthy processing time usually indicates strong performance. Very low times with unusually high throughput should be reviewed for bulk-closing.

Use the selected Viewing Period consistently when comparing Operators or shifts.